

## Techlam Glulamated Timber Products

# COATINGS

Version 1.2 June 2024

## GLULAMINATED TIMBER COATINGS

### Introduction

Techlam supplies Glulam timber products treated to H1.2, H3.1, H3.2 and H5. For this level of treatment, a coating is not required but over time the timber will become grey in colour and checking and fine cracking can occur. These changes only impact the appearance and have no impact on the structural performance. To prevent these changes we recommend that a paint or stain system is applied. This should be applied within 24 hours of receipt of delivery of the product. A light sand and reapplication of the coating is all that is required to maintain the original appearance. Coatings give your glulamated timber the protection to stay in great condition. Coatings are for Interior or Exterior uses, forming a layer to protect your timber and prevent cracking, discolouration and wear.

### Which Coatings to Use

We recommend a lighter coloured stain with an LRV of over 40%  
A Light Reflectant Value measures the intensity of the stain. Stains are commonly tested on Cedar. Our product is Pine, so whatever you choose will be much lighter in colour. Get us to do up a few samples for your project if required. The LRV is a rating that covers all paints and stains and changes due to the amount of coats and what surface it's applied to. Techlam cannot supply a specific LRV Rating for your stain, but we recommend light stains. Meaning there is less chance of the timber cracking from heat. An Oil based product always works best, as it seals the product well, protecting from the inside out and there is no chance of distortion from a Water based product.

### Recommended Products

**Resene Woodsman Wood Oil Stain**  
Stain for exterior timber is a penetrating solventborne oil stain matching the needs of timber with your desire to achieve the most natural appearance possible.

#### Sikkens

Sikkens Cetol HLSe is a transparent, satin woodcare product for interior and exterior use. Its woodstain like qualities ensure the timber grain remains highly visible.

#### WOCA Denmark

Exterior oil provides a strong water and dirt-repellent surface that prevents the growth of mould and fungus, as well as providing UV protection. It is fast-drying, and enhances the natural colour and grain of wood.

#### Dryden

Dryden WoodOil delivers better care, protection and a premium finish to your timber. Our formulas not only maintain wood's visual appeal but protect its core strength and durability too.

#### Cutek

CUTEK® Extreme CD50 is made in New Zealand for New Zealand conditions. CUTEK® Extreme CD50 diffuses throughout wood to control liquid and gas phase moisture, to minimise warping, cupping and splitting. By improving the dimensional stability of wood, CUTEK® Extreme CD50 improves the service life of your timber.